

RECEIVED
CENTRAL FAX CENTER

SEP 26 2007

Application No. 10/823,389
Filed: 4/13/04
TC Art Unit: 2877
Confirmation No.: 3371AMENDMENT TO THE CLAIMS

1. (Withdrawn) A method for measuring phase of light passing through a portion of a sample comprising the steps of:
 providing a first wavelength of light;
 directing light of the first wavelength along a first optical path and a second optical path, the first optical path extending onto a sample medium to be measured and the second path undergoing a change in path length; and
 detecting light from the sample medium and light from the second optical path to measure a change in phase of light passing through two separate points on the sample medium.
2. (Withdrawn) The method of Claim 1 wherein the medium comprises biological tissue.
3. (Withdrawn) The method of Claim 1 further comprising at least one of a photodiode array and a photodiode-coupled fiber bundle to image the phase of the sample at a plurality of positions simultaneously.
4. (Withdrawn) The method of Claim 1 further comprising the step of frequency shifting the light in the second optical path.
5. (Withdrawn) The method of Claim 1 further comprising the step of detecting the change in phase by at least two photo detectors.

Application No. 10/823,389

Filed: 4/13/04

TC Art Unit: 2877

Confirmation No.: 3371

6. (Withdrawn) The method of Claim 1 further comprising providing a helium-neon laser light source that emits the first wavelength.

7. (Withdrawn) The method of Claim 1 further comprising providing a low coherence light source.

8. (Withdrawn) A method for measuring a phase characteristic of light passing through a portion of a sample, comprising the steps of;

providing a first signal and a second signal generated by a first light source and a second light source, respectively, the second light source being a low coherence source;

directing the first signal and the second signal along a first optical path and a second optical path;

varying a path length difference between the first optical path and the second optical path;

generating an output signal indicative of the sum of the first and the second signal with an optical path delay between them;

modulating the output signal at an interferometer lock modulation frequency; and

determining the phase of the sample by the time evolution of the interferometer lock phase.

9. (Withdrawn) The method of Claim 8 wherein the first signal and second signal are low coherence signals.

10. (Withdrawn) The method of Claim 8 further comprising demodulating the first signal by using one of a mixer or lock-in amplifier.

Application No. 10/823,389

Filed: 4/13/04

TC Art Unit: 2877

Confirmation No.: 3371

11. (Withdrawn) The method of Claim 8 further comprising electronically generating the interferometer lock phase.

12-20 (Cancelled)

21. (Original) A method for imaging a sample comprising the steps of:

illuminating a sample, the light originating from a point on the sample having a low frequency spatial component and high frequency spatial components;

interfering along a common optical path the high frequency spatial components with the low frequency spatial component to produce a first intensity signal;

shifting the phase of the low frequency spatial component to produce a first phase shifted low frequency spatial component;

interfering along a common optical path the high frequency spatial components with the first phase shifted low frequency spatial component to produce a second intensity signal;

shifting the phase of the low frequency spatial component to produce a second phase shifted low frequency spatial component;

interfering along a common optical path the high frequency spatial components with the second phase shifted low frequency spatial component to produce a third intensity signal;

shifting the phase of the low frequency spatial component to produce a third phase shifted low frequency spatial component;

interfering along a common optical path the high frequency spatial components with the third phase shifted low frequency

Application No. 10/823,389

Filed: 4/13/04

TC Art Unit: 2877

Confirmation No.: 3371

spatial component to produce a fourth intensity signal;

generating a phase image of the point on the sample based at least in part on the first intensity signal, the second intensity signal, the third intensity signal and the fourth intensity signal.

22. (Original) The method of claim 21, further comprising the step of:

generating a phase image of the sample by repeating the steps of claim 1 for a plurality of points on the sample.

23. (Original) The method of claim 21, wherein the step of illuminating comprises illuminating the sample using a transmission illumination.

24. (Original) The method of claim 21, wherein the step of illuminating comprises illuminating the sample using a reflective illumination.

25. (Original) The method of claim 21, wherein the step of illuminating comprises illuminating the sample by both transmission and reflective illumination.

26. (Original) The method of claim 21, wherein the step of illuminating comprises illuminating the sample with a superluminescent light source.

27. (Original) The method of claim 21, further comprising the step of controlling the amplitude of at least one of the high

Application No. 10/823,389

Filed: 4/13/04

TC Art Unit: 2877

Confirmation No.: 3371

frequency spatial components.

28. (Original) The method of claim 21, further comprising the step of controlling the amplitude of at least one of the low frequency spatial component and phase shifted low frequency spatial components.

29. (Original) The method of claim 21, wherein each step of shifting the phase shifts the phase of the low frequency spatial component by substantially $n / 2$.

30. (Original) The method of claim 21, wherein the step of generating a phase image is based at least in part on the equation.

$$\phi(x, y) = \arctan \left[\frac{\sqrt{\beta} \cdot \sin[\Delta\phi(x, y)]}{1 + \sqrt{\beta} \cdot \cos[\Delta\phi(x, y)]} \right],$$

where

$$\tan[\Delta\phi(x, y)] = \frac{I_{\text{image}}(x, y; 3\pi/2) - I_{\text{image}}(x, y; \pi/2)}{I_{\text{image}}(x, y; 0) - I_{\text{image}}(x, y; \pi)}, \text{ and}$$

$I_{\text{image}}(x, y; \delta)$ is the intensity signal for a point (x, y) on the sample surface generated by interfering the high frequency spatial components with a low frequency spatial component of phase shift δ , and $\beta = I_1/I_0$ represents the ratio between the intensity associated with the high frequency spatial component, I_1 , and the intensity associated with the low frequency spatial component, I_0 .

Application No. 10/823,389

Filed: 4/13/04

TC Art Unit: 2877

Confirmation No.: 3371

31. (Original) The method of claim 22, wherein the step of generating a phase image of the sample comprises generating a phase image of the sample with a phase sensitivity of greater than about $\lambda/1000$.

32. (Original) The method of claim 22, wherein the sample comprises a biological tissue.

33. (Original) The method of claim 23, wherein the sample comprises a semiconductor wafer.

34-46 (Cancelled)

47. (Withdrawn) A fiber optic probe for optically imaging a sample, comprising:

a housing having a proximal end and a distal end;
a fiber collimator in the proximal end of the housing coupled to a light source;

and

a graded index lens in the distal end of the housing, the lens having a first and second surface wherein the first surface is the reference surface and wherein numerical aperture of the probe provides efficient light gathering from scattering surfaces of a sample.

48. (Withdrawn) The probe of Claim 47 further comprising a system comprising mounting the fiber optic probe on a translator stage to

Application No. 10/823,389

Filed: 4/13/04

TC Art Unit: 2877

Confirmation No.: 3371

perform at least one of two-dimensional phase imaging and three-dimensional confocal phase imaging.

49. (Withdrawn) The probe of Claim 48 wherein the translator stage comprises a scanning piezo translator.

50. (Withdrawn) The probe of Claim 47 wherein the numerical aperture of the probe is in a range of approximately 0.4 to 0.5.

51. (Withdrawn) The probe of Claim 47 wherein the probe images in-vivo biological tissue.

52. (Withdrawn) A method for non-contact optical measurement of an eye, comprising the steps of:

providing a light source that generates a first signal and a second signal; providing a first optical path from the interferometer in communication with the eye and a second optical path from the interferometer in communication with a reference; and

measuring a first heterodyne signal with light returning from the eye and the reference, respectively, in response to the first signal and the second signal; and

determining a phase of the first heterodyne signal indicative of the phase of the light returning from the eye relative to the light returning from the reference.

53. (Withdrawn) The method of Claim 52 wherein the first signal is a low coherence signal.

Application No. 10/823,389

Filed: 4/13/04

TC Art Unit: 2877

Confirmation No.: 3371

54. (Withdrawn) The method of Claim 52 wherein the light source is one of a superluminescent diode and multimode laser diode.

55. (Withdrawn) The method of Claim 52 wherein the interferometer further comprises a first path and a second path, the second path having acousto-optic modulators.

56. (Withdrawn) The method of Claim 52 further comprising an optical pathway including an optical fiber.

57. (Currently Amended) A method for imaging a sample comprising the steps of:

illuminating a sample to generate a low frequency spatial light component and a high frequency spatial light component;
~~interfering spatially separating,~~ along a common optical path, the high frequency spatial light component ~~with~~ from the low frequency spatial light component;

shifting a phase of the low frequency spatial light component; and

generating a phase image of ~~the point on a~~ region of the sample.

58. (Previously Presented) The method of claim 57, further comprising the step of:

generating a phase image of the sample by repeating the steps of claim 1 for a plurality of points on the sample.

59. (Previously Presented) The method of claim 57, wherein the step of illuminating comprises illuminating the sample using a

Application No. 10/823,389

Filed: 4/13/04

TC Art Unit: 2877

Confirmation No.: 3371

transmission illumination.

60. (Previously Presented) The method of claim 57, wherein the step of illuminating comprises illuminating the sample using a reflective illumination.

61. (New) The method of claim 57 further comprising using a spatial light modulator to shift the phase.

62. (New) The method of claim 61 further comprising using a computer to control the spatial light modulator and adjust the phase shift.